



# T1/E1/CEPT/ISDN-PRI TRANSFORMERS DUAL PORT SURFACE MOUNT TYPE

- Quad SMT package contains both transmit & receive transformers
- Models matched to leading Transceiver IC's
- Surface mount closed header construction
- UL Recognized
- Standard operating temp: 0°C to +70°C (see footnote)
- Industrial operating temp: -40°C to +85°C (see footnote)

## Electrical Specifications @25°C


Part Number	Turns Ratio ( $\pm 5\%$ )	OCL PRI (mH Min)	LL (mH Min)	CWW (pF Max)	DCR(25°C) ( $\Omega$ Max)	HI-POT	Primary Pins
	Pri:Sec	10KHz ,0.1V	100KHz J0.1V	100KHz 0.2V	Pri	1500VAC	24-22,4-6,18-16,10-12
ATE2401S_	1CT:1CT&1CT:2CT	1.2&1.2	0.8&0.8	35&35	0.8 $\Omega$		

\*Complete part number by inserting "S" for Standard Temp or "I" for Industrial Temp.

All specifications subject to change without notice.

## MECHANICAL

ATE2401S\_



Unless otherwise specified all tolerances are:  $\pm 0.25$  in mm

## SCHEMATICS

ATE2401S\_

